





MANITOU MT 732



Maximum height reach: 1.15 m

As per standard EN 1459 annex B



		MT 732
	Lifting capacity at 500 mm from forks heels	3200 kg
	Break-out force (ISO 8313)	7400 daN
	Lifting height	6.90 m
	Time: laden/unladen (in sec)	
	Lifting	7.20/7.20
	Lowering	5.50/5.80
	Extension	6.50/6.50
	Retraction	5.40/5.90
	Crowd	2.90
	Dump	2.80
	Tyres	400/80-24 156A8 IND TL PCL
	Forks (mm) Length x width x thickness	1200 x 125 x 45
	Braking	multiple-disk hydraulic brakes with oil bath on front and rear axles
	PERKINS STAGE III A Engine	1104D - 44T
	Cubic capacity	4 cyl. - 4400 cm ³
	Power at 2200 rpm (ISO/TR 14396)	95 HP/70 kW
	Max. torque at 1400 rpm (ISO/TR 14396)	392 Nm
	Injection	direct
	Cooling	water
	Transmission	torque converter
	Gearbox	electro-hydraulic
	Number of gears (forward/reverse)	4/4
	Max. travel speed	25 kph*
	Hydraulics	
	Gear pump	105 l/min - 250 bar
	Capacities	
	Cooling system	18.50 l
	Engine oil	11 l
	Hydraulic oil	128 l
	Fuel	120 l
	Unladen weight (with forks)	7330 kg
	Width overall	2.26 m
	Height overall	2.30 m
	Length overall	4.77 m
	Turning radius (outer wheels)	3.67 m
	Ground clearance	0.45 m
	Drawbar pull	9280 daN
	Noise at driving position (LpA)	78 dB
	Environmental noise (LWA)	105 dB
	Vibration to whole hand/arm	<2.50 m/s ²
	Vibration on driver's body	1.015 m/s ²

mm	D2 3894	I 763	P3 53°	V1 1250
A 1200	E 5966.6	J 865	R 3460	V2 3667
B 2560	F 1846	K 1040	S 7590.6	W 2260
C 1443.6	F1 1846	L 45	T 3555	Y 11.9°
C1 1537	G 455	N 1690	U1 2300	Z 113.8°
D 4766.6	G1 440	O 125	U2 2550	
D1 4860	G2 440	P2 47.5°	V 4805	