



# TEREX TA3

## Specifications

### Performance

	TA3	TA3H	TA3S	TA3SH
Payload (kg)	3000	3000	3000	3000
Unladen Weight (kg)	2260	2320	2550	2620
Skip Capacity - Water (ltr)	1250	1250	1000	1000
- Struck (ltr)	1600	1600	1500	1500
- Heaped (ltr)	1950	1950	1870	1870
Engine	Kubota V2203M			
- Net Power - kW (hp)	32.4 (43.5)			
- Displacement	2197 cc			
- Maximum Torque	147 Nm			
Tyre Size	11.5/80x15.3x8ply			
Drive	3/1 Manual - permanent 4WD	2/2 Hydrostatic - permanent 4WD	3/1 Manual - permanent 4WD	2/2 Hydrostatic - permanent 4WD
Max Travel Speed - mph (kph)	11.8 (19.0)	11.8 (19.0)	11.8 (19.0)	11.8 (19.0)
Gradeability	25 %	25 %	25 %	25 %
Fuel Tank Capacity	37 Litres	37 Litres	37 Litres	37 Litres
Hydraulic Tank Capacity	37 Litres	37 Litres	37 Litres	37 Litres

### Hydraulic System (Gear Pump)

	TA3	TA3H	TA3S	TA3SH
Flow rate	30 l/min	30 l/min	30 l/min	30 l/min
Operating Pressure	172 bar	172 bar	172 bar	172 bar

### Dimensions (mm)

	TA3	TA3H	TA3S	TA3SH
A Total Length	3700	3700	3790	3790
B Total Width (not shown)	1950	1950	1840	1840
C Height to Top of Steering Wheel	1860	1890	1860	1890
D Wheelbase	1950	1950	1950	1950
E Height to Front Lip of Skip (untipped)	1430	1460	1500	1530
F Ground Clearance (Loaded)	280	242	280	242
G Height to Top of ROPS (raised)	2660 (+200 over Beacon)	2690 (+200 over Beacon)	2660 (+200 over Beacon)	2690 (+200 over Beacon)
H Height to Front Lip of Skip (tipped)	240	270	1100	1130
Turning Radius to Outside of Skip	4350 mm	4350 mm	4665 mm	4665 mm
Steering Angle	± 30°	± 30°	± 30°	± 30°
Oscillation	± 10.5°	± 10.5°	± 10.5°	± 10.5°
Tipping Type	Forward	Forward	Swing	Swing



**TA3  
TA3S**      **TA3H  
TA3SH**

## Dimensions

B = Overall Width (not shown)

