



TEREX TA3

Specifications

Performance				
	TA3	TA3H	TA3S	TA3SH
Payload (kg)	3000	3000	3000	3000
Unladen Weight (kg)	2260	2320	2550	2620
Skip Capacity - Water (ltr)	1250	1250	1000	1000
- Struck (ltr)	1600	1600	1500	1500
- Heaped (ltr)	1950	1950	1870	1870
Engine	Kubota V2203M			
- Net Power - kW (hp)	32.4 (43.5)			
- Displacement	2197 cc			
- Maximum Torque	147 Nm			
Tyre Size	11.5/80R15.3poly			
Drive	3/1 Manual - permanent 4WD	2/2 Hydrostatic - permanent 4WD	3/1 Manual - permanent 4WD	2/2 Hydrostatic - permanent 4WD
Max Travel Speed - mph (kph)	11.8 (19.0)	11.8 (19.0)	11.8 (19.0)	11.8 (19.0)
Gradeability	25 %	25 %	25 %	25 %
Fuel Tank Capacity	37 Litres	37 Litres	37 Litres	37 Litres
Hydraulic Tank Capacity	37 Litres	37 Litres	37 Litres	37 Litres

Hydraulic System (Gear Pump)				
	TA3	TA3H	TA3S	TA3SH
Flow rate	30 l/min	30 l/min	30 l/min	30 l/min
Operating Pressure	172 bar	172 bar	172 bar	172 bar

Dimensions (mm)				
	TA3	TA3H	TA3S	TA3SH
A Total Length	3700	3700	3790	3790
B Total Width (not shown)	1950	1950	1840	1840
C Height to Top of Steering Wheel	1860	1890	1860	1890
D Wheelbase	1950	1950	1950	1950
E Height to Front Lip of Skip (untipped)	1430	1460	1500	1530
F Ground Clearance (Loaded)	280	242	280	242
G Height to Top of ROPS (raised)	2660 (+200 over Beacon)	2690 (+200 over Beacon)	2660 (+200 over Beacon)	2690 (+200 over Beacon)
H Height to Front Lip of Skip (tipped)	240	270	1100	1130
Turning Radius to Outside of Skip	4350 mm	4350 mm	4665 mm	4665 mm
Steering Angle	± 30°	± 30°	± 30°	± 30°
Oscillation	± 10.5°	± 10.5°	± 10.5°	± 10.5°
Tipping Type	Forward	Forward	Swing	Swing



TA3
TA3S

TA3H
TA3SH

Dimensions

B = Overall Width (not shown)

